

Concrete Conveying Hose



Application	Delivery of cement paste, mortar and other highly abrasive materials. Used for concrete placement for end of concrete pump truck, grouting from pile driver.
Branding:	Techfluid HN85 CONCRETE CONVEYING HOSE TECHFLUID WP 85 BAR
Hose structure	
Tube	Black smooth conductive rubber, abrasion resistant synthetic rubber.
Reinforcement	High-tension steel cable
Cover:	Black, abrasion resistant synthetic rubber, ageing resistance.
Temperature Range	-30°C to + 100°C

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		MBR (mm)	Weight (kg/m)	Length Max (m)
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)			
NH8532	2	51	2.8	71	85	1,232	200	2,900	35	3.0	70
NH8540	2 ½	64	2.5	89	85	1,232	200	2,900	40	4.7	70
NH8548	3	76	4.0	103	85	1,232	200	2,900	45	6.7	70
NH8550	3.1	80	4.2	107	85	1,232	200	2,900	50	7.1	70
NH8564	4	102	5.0	126	85	1,232	200	2,900	70	8.9	70
NH8580	5	127	6.1	154	85	1,232	200	2,900	90	11.1	70
NH8596	6	152	7.2	184	85	1,232	200	2,900	100	15.1	70