

Multi-purpose Suction & Discharge Hose



Application	For delivery of gasoline, diesel oil, fuel oil with aromatic content up to 50%, also can be applicable for seawater, fresh water, mud and air and other general purposes fluid.
Branding:	Techfluid HS10 MULTI-PURPOSE DISCHARGE HOSE TECHFLUID WP10 BAR
Hose structure	
Tube	Black, nitrile rubber, oil resistance, seawater resistance, high temperature resistance, acid & alkali resistance.
Reinforcement	High tension textile fabric, helix steel wire and anti-static copper wire
Cover	Black, BR/Neoprene blended elastomer, wear resistance, ozone & ageing resistance, oil resistance, heat resistance.
Temperature Range	-30°C to + 100°C

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety (m)	MBR (mm)	Weight (Kg/m)	Length Max (m)	Negative Pressure (Kpa)
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)					
HS1096	6	152	7.00	178	10	150	40	600	4	800	10	40	-90
HS1128	8	203	9.37	238	10	150	40	600	4	1,100	23	40	-90
HS1160	10	254	11.38	289	10	150	40	600	4	1,300	26	20	-90
HS1192	12	305	13.50	343	10	150	40	600	4	1,600	34	20	-90
HS1224	14	355	15.55	395	10	150	40	600	4	2,200	38	20	-90
HS1256	16	405	17.52	445	10	150	40	600	4	2,500	43	20	-90