










Oil Delivery Hose



Application	For delivery gasoline, diesel oil, fuel oil with aromatic content up to 50% also applicable for seawater, fresh water, mud, air and other general purposes.
Branding	Techfluid SY40 OIL DELIVERY HOSE TECHFLUID WP 40 BAR
Hose structure	
Tube	Black smooth nitrile rubber, oil resistance, seawater resistance, high temperature resistance, acid & alkali resistance
Reinforcement	High tension textile fabric, anti-static copper wire
Cover	Black, blended chloroprene rubber and butadiene rubber, wear resistance, ozone & ageing resistance, oil resistance, heat resistance
Temperature Range	-30°C to + 100°C
Length	Maximum length: 100m

 Type	 Internal Diameter		 Outside Diameter		 Working Pressure		 Burst Pressure		 Safety	 MBR	 Weight	 Length Max
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	(mm)	(Kg/m)	(m)
SY4012	¾	19	1.22	33	40	600	160	2,400	4	110	0.8	100
SY4016	1	25	1.54	43	40	600	160	2,400	4	150	1.2	100
SY4020	1 ¼	32	1.85	50	40	600	160	2,400	4	200	1.4	100
SY4024	1 ½	38	2.09	57	40	600	160	2,400	4	250	1.8	100
SY4032	2	51	2.64	72	40	600	160	2,400	4	350	2.4	100
SY4040	2 ½	64	3.11	85	40	600	160	2,400	4	420	3.0	100
SY4048	3	76	3.62	98	40	600	160	2,400	4	500	3.5	100

Rev-00