

Oil Delivery Hose



Application	For delivery gasoline, diesel oil, fuel oil with aromatic content up to 50% also applicable for seawater, fresh water, mud, air and other general purposes.
Branding	Techfluid SY10 OIL DELIVERY HOSE TECHFLUID WP 10 BAR
Hose structure	
Tube	Black smooth nitrile rubber, oil resistance, seawater resistance, high temperature resistance, acid & alkali resistance
Reinforcement	High tension textile fabric, anti-static copper wire
Cover	Black, blended chloroprene rubber and butadiene rubber, wear resistance, ozone & ageing resistance, oil resistance, heat resistance
Temperature Range	-30°C to + 100°C
Length	Maximum length: 100m

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety Factor	MBR (mm)	Weight (Kg/m)	Length Max (m)
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)				
SY1048	3	76	3.62	92	10	150	40	600	4	500	2.5	100
SY1064	4	102	4.69	119	10	150	40	600	4	650	3.6	100
SY1080	5	127	5.75	146	10	150	40	600	4	800	5.7	100
SY1096	6	152	6.77	172	10	150	40	600	4	950	7.1	100
SY10128	8	203	9.02	229	10	150	40	600	4	1,400	11.3	100

Rev-00