

# Potable Water Hose (Hard Wall)



Application	For suction & discharge of potable water.
Branding	<b>Techfluid XS20 POTABLE WATER SUCTION &amp; DELIVERY TECHFLUID WP 20 BAR</b>
Hose structure	
Tube	White, non-toxic and odourless natural rubber
Reinforcement	High tension textile, helix steel wire
Cover	Blue, nitrile rubber/PVC, wear resistance, ozone resistance, hydrocarbon resistance.
Temperature Range	-30°C to + 100°C
Length	Maximum length: 60m
<b>Certified with FDA registration</b>	

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety	MBR	Weight	Length Max	Negative pressure
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	(mm)	(Kg/m)	(m)	(Kpa)
XS2048	3	76	3.82	97	20	300	80	1,200	4	400	4.0	60	-90
XS2064	4	102	5.08	129	20	300	80	1,200	4	550	6.5	60	-90
XS2080	5	127	6.06	154	20	300	80	1,200	4	650	8.3	60	-90
XS2096	6	152	7.01	180	20	300	80	1,200	4	800	10.6	60	-90

Rev-00