

Oil Suction & Delivery Hose



Application	For suction & discharge gasoline, diesel oil, fuel oil with aromatic content up to 50%, also applicable for seawater, fresh water, mud, air and other general purposes.
Branding	Techfluid XY20 OIL SUCTION & DELIVERY HOSE TECHFLUID WP 20 BAR
Hose structure	
Tube	Black smooth nitrile rubber, oil resistance, seawater resistance, high temperature resistance, acid & alkali resistance
Reinforcement	High tension textile fabric, helix steel wire and anti-static copper wire
Cover	Black, blended chloroprene rubber and butadiene rubber, wear resistance, ozone & ageing resistance, oil resistance, heat resistance
Temperature Range	-30°C to + 100°C
Length	Maximum length: 100m

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety	MBR	Weight	Length Max	Negative pressure
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	(mm)	(Kg/m)	(m)	(Kpa)
XY2048	3	76	3.82	97	20	300	80	1,200	4	400	4.0	100	-90
XY2064	4	102	5.08	129	20	300	80	1,200	4	550	6.5	100	-90
XY2080	5	127	6.06	154	20	300	80	1,200	4	650	8.3	100	-90
XY2096	6	152	7.09	180	20	300	80	1,200	4	800	10.6	100	-90

Rev-00