

Oil Suction & Delivery Hose



Application	For suction & discharge gasoline, diesel oil, fuel oil with aromatic content up to 50%, also applicable for seawater, fresh water, mud, air and other general purposes.
Branding	Techfluid XY40 OIL SUCTION & DELIVERY HOSE TECHFLUID WP 40 BAR
Hose structure	
Tube	Black smooth nitrile rubber, oil resistance, seawater resistance, high temperature resistance, acid & alkali resistance
Reinforcement	High tension textile fabric, helix steel wire and anti-static copper wire
Cover	Black, blended chloroprene rubber and butadiene rubber, wear resistance, ozone & ageing resistance, oil resistance, heat resistance
Temperature Range	-30°C to + 100°C
Length	Maximum length: 100m

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety	MBR	Weight	Length Max	Negative pressure
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	(mm)	(Kg/m)	(m)	(Kpa)
XY4048	3	76	4.72	97	40	600	160	2,400	4	456	5.5	100	-90
XY4064	4	102	5.08	129	40	600	160	2,400	4	612	7.4	100	-90
XY4080	5	127	6.65	154	40	600	160	2,400	4	762	13.8	100	-90

Rev-00