Jetting Hose

***Previously branded* – TECHFLOW FLEXIBLES**

Application	After Jackup Rig finishes well drilling, pile shoes should be pulled out for moving the pile leg, mud around pile shoe should be flushed off by using high-pressure seawater so as to facilitate pile pulling. Jetting hose is high-pressure flexible connection between main deck of platform and seawater pipe line among pile legs.
Hose Branding	**Techfluid J3K JETTING HOSE TECHFLUID WP 3000 PSI**
Hose structure	
Tube	Nitrile rubber based liner, oil resistance, seawater resistance, high temperature resistance and ageing resistance.
Reinforcement	High tension steel cable
Cover	Neoprene rubber based cover, fire-proof, wear resistance, oil resistance, ozone & ageing resistance, UV resistance, which is applicable to marine environment
Temperature Range	-30°C to + 100°C

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety	MBR	Weight	Length Max
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	(m)	(Kg/m)	(m)
J3032	2	51	3.39	86	210	3,000	840	12,000	4	900	10.4	70
J3040	2 ½	64	3.94	100	210	3,000	840	12,000	4	900	12.4	70
J3048	3	76	4.37	111	210	3,000	840	12,000	4	1,200	15.1	70
J3056	3 ½	89	5.00	127	210	3,000	840	12,000	4	1,400	19.2	70
J3064	4	102	5.47	139	210	3,000	840	12,000	4	1,400	21.4	70
J3080	5	127	7.36	187	210	3,000	840	12,000	4	1,500	41.5	70
J3096	6	152	8.5	216	210	3,000	840	12,000	4	1,600	58	70