


Roof Drain Hose







Application	For floating roofs on oil and petroleum tanks that are designed to collect rain water. Hose systems designed for immersion inside storage tanks to drain rain water from roof to a tank floor and out. Also used on a wide range of PH solutions and chemicals, also suitable for 100% aromatic hydrocarbons. ZP10 ROOF DRAIN HOSE WP 10 BAR								
Branding									
Hose structure									
Tube	Black CR Blend, abrasion and weather resistant								
Reinforcement	Synthetic textile cord and helix steel wire								
Cover	Black, blended nitrile rubber for hydrocarbons with aromatic content, wear resistance, ozone & ageing resistance,								
	oil resistance, heat resistance								
Temperature Range	-25°C to + 100°C								
Length	Maximum length: 100m								

\$10°	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety	d	MBR	WT Weight	Length Max
Type	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)	Factor	Armored		(Kg/m)	(m)
ZP1064	4	102	4.9	124	10	150	40	600	4	No	600	5.8	100
ZP1096	6	152	7.2	182	10	150	40	600	4	No	900	12.1	100
ZP10128	8	203	9.6	244	10	150	40	600	4	No	1,100	20.5	100
ZK1064	4	102	5.2	132	10	150	40	600	4	Yes	600	12.9	100
ZK1096	6	152	7.4	190	10	150	40	600	4	Yes	900	22.6	100
ZK10128	8	203	9.9	252	10	150	40	600	4	Yes	1,100	43.4	100