

Jetting Hose



Application	After Jackup Rig finishes well drilling, pile shoes should be pulled out for moving the pile leg, mud around pile shoe should be flushed off by using high-pressure seawater so as to facilitate pile pulling. Jetting hose is high-pressure flexible connection between main deck of the platform and seawater pipe line among pile legs.
Hose Branding	Techfluid J2K JETTING HOSE TECHFLUID WP 2000 PSI
Hose structure	
Tube	Nitrile rubber based liner, oil resistance, seawater resistance, high temperature resistance and ageing resistance.
Reinforcement	High tension steel wire
Cover	Synthetic rubber consisting of chloroprene rubber which is an anti-flaming, wear resistant, ozone ageing resistant and ultraviolet light and applicable to marine environment.
Temperature Range	-30°C to + 100°C

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety Factor	MBR (m)	Weight (Kg/m)	Length Max (m)
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)				
J2032	2	51	3.03	77	140	2,000	560	8,000	4	900	7.0	70
J2040	2 ½	64	3.58	91	140	2,000	560	8,000	4	900	9.5	70
J2048	3	76	4.61	117	140	2,000	560	8,000	4	1,200	15.5	70
J2056	3 ½	89	4.84	123	140	2,000	560	8,000	4	1,400	15.8	70
J2064	4	102	5.24	133	140	2,000	560	8,000	4	1,400	16.0	70
J2080	5	127	6.69	170	140	2,000	560	8,000	4	1,450	28.5	70
J2096	6	152	7.68	195	140	2,000	560	8,000	4	1,500	35.5	70