

Jetting Hose



Application	After Jackup Rig finishes well drilling, pile shoes should be pulled out for moving the pile leg, mud around pile shoe should be flushed off by using high-pressure seawater so as to facilitate pile pulling. Jetting hose is high-pressure flexible connection between main deck of platform and seawater pipe line among pile legs.
Hose Branding	Techfluid J3K JETTING HOSE TECHFLUID WP 3000 PSI
Hose structure	
Tube	Nitrile rubber based liner, oil resistance, seawater resistance, high temperature resistance and ageing resistance.
Reinforcement	High tension steel cable
Cover	Neoprene rubber based cover, fire-proof, wear resistance, oil resistance, ozone & ageing resistance, UV resistance, which is applicable to marine environment
Temperature Range	-30°C to + 100°C

Type	Internal Diameter		Outside Diameter		Working Pressure		Burst Pressure		Safety Factor	MBR (m)	Weight (Kg/m)	Length Max (m)
	(inch)	(mm)	(inch)	(mm)	(bar)	(psi)	(bar)	(psi)				
J3032	2	51	3.39	86	210	3,000	840	12,000	4	900	10.4	70
J3040	2 ½	64	3.94	100	210	3,000	840	12,000	4	900	12.4	70
J3048	3	76	4.37	111	210	3,000	840	12,000	4	1,200	15.1	70
J3056	3 ½	89	5.00	127	210	3,000	840	12,000	4	1,400	19.2	70
J3064	4	102	5.47	139	210	3,000	840	12,000	4	1,400	21.4	70
J3080	5	127	7.36	187	210	3,000	840	12,000	4	1,500	41.5	70
J3096	6	152	8.5	216	210	3,000	840	12,000	4	1,600	58	70